# 24" GAS COOKTOP

#### MATTEO 400 SERIES



FULGOR 

# MODEL CODE

ð

# F4MGK24MB1



Heavy-Duty Grates

Continuous Grate Surface

Dual-Flame Burner

Automatic Reignition System

Americans with Disabilities Act †

#### DESCRIPTION

The Matteo 400 Series 24" gas cooktop seamlessly blends sleek style with practical functionality. Its highquality brass burners and sophisticated matte black porcelain finish enhance both elegance and ease of cleaning. The contemporary design adapts beautifully to various kitchen styles, while durable cast iron grates provide a stable and user-friendly surface that's easy to clean. With a continuous cooking surface, a versatile burner layout, and the added safety of automatic re-ignition, it's perfect for everyday meals or gourmet creations, delivering consistent performance and elevating your culinary experience.

#### **FEATURES**

4 gas burners with 1 dual-flame burner (front-left) Matte Brass burners Automatic re-ignition system Heavy-duty continuous cast iron grates Durable and easy-to-clean Matte Black porcelain base Convertible to Liquid Propane

#### INCLUDED ACCESSORIES

41091255	
49000100543	L

Installation Kit \_P Conversion Kit

## **OPTIONAL ACCESSORIES**

FMWOK	Wok Ring
FMSIM	Simmer Plate

† To achieve full ADA compliance, please consult the current ADA requirements for product installation instructions.

# FULGOR MILANO 24" GAS COOKTOP MODEL CODE ð F4MGK24MB1 MATTEO 400 SERIES 20 - 1/2" 24 - 3/8" (520) (620) 3" (75) MAX MAX 23-5/8" 19 -11/16" (600)

(500)

MIN

19 - 5/8"

(498)

MIN

23 - 1/2"

(597)

MODEL CODE	24" GAS COOKTOP F4MGK24MB1
GENERAL DETAILS	
Finish	Matte Black Porcelain
Control Type	Knobs
Fuel Type	Gas (NG or LP)
Heavy-Duty Cast Iron Grates	2
Cooking Zones	4
Sealed Burners	Yes
DIMENSIONS / WEIGHT	
Product Width, in. (mm)	24-3/8 (620)
Product Height, in. (mm)	5-1/4 (132)
Product Depth, in. (mm)	20-1/2 (520)
Cutout Width (min-max), in. (mm)	23-1/2 - 23-5/8 (597 - 600)
Cutout Height (min), in. (mm)	3-3/8 (86)
Cutout Depth (min-max), in. (mm)	19-5/8 - 19-11/16 (498 - 500)
Net Weight, Ibs. (kg)	29 (13)
POWER / RATINGS (120 V, 60 Hz)	
Power (min-max) (Front-L)	850 BTU/h (250 W) - 20000 BTU/h (5865 W)
Power (min-max) (Front-R)	1000 BTU/h (295 W) - 4000 BTU/h (1175 W)
Power (min-max) (Rear-L)	1300 BTU/h (380 W) - 8000 BTU/h (2350 W)
Power (min-max) (Rear-R)	2200 BTU/h (645 W) - 1200 BTU/h (2520 W)
TECHNICAL DETAILS	
Amperage Rating	0.1 A
Maximum Power	44000 BTU/h (12900 W)
Power Cable	3 Prong Nema 5 - 15P
Power Cable Length, in. (mm)	51 (1300)
Electrical Circuit	120 V - 60 Hz - 15 A
LP Kit Included	Yes
INSTRUCTIONS FOR USE	
Use & Care Manual / Installation Manual	English / French / Spanish
WARRANTY	
Limited Warranty	Parts and Labor (2-year)